



APPROXIMATE WEIGHTS:
M2A = 45 Kg
GM2 = 47 Kg

NOTE: THIS IS THE COMPARISON WITH THE STANDARD GM2 MOTOR

THERE IS ALSO A SPECIAL VERSION OF THE GM2 WHICH HAS SLOTS ON 195 PCD (ONLY AVAILABLE WITH UNI MALE SPLINE & SELECTED DISPLACEMENTS)

ALSO - 5 OFF M12 TAPPED HOLES ON 195 PCD CAN BE SUPPLIED ON THE GM2 (NOT SHOWN)

TOLERANCES:
UNLESS OTHERWISE STATED, MACHINING TOLERANCES ARE TO BE:
PLUS/MINUS 0.125 mm



This drawing is the property of SAI (GB) Ltd and is subject to return upon request. The drawing includes confidential proprietary information and is loaned in confidence with the understanding that it is not to be copied or reproduced without express permission, and that it will not be used adversely to SAI (GB) Ltd. Whilst every effort has been made to ensure the accuracy of the information contained within this drawing, SAI (GB) Ltd cannot be held responsible for any errors or omissions. All patent rights are reserved.

SAI (GB) Limited
Unit 8, Honeywood Road Business Park
Basildon, Essex.
SS14 3HW

DESCRIPTION
MAIN DIFFERENCES BETWEEN
M2A and GM2 HYDRAULIC MOTOR

DRAWING No
GM2 AGAINST M2A

DRAWN	PJW	DATE	14/05/02	CLIENT		REF No	
CHECKED		DATE		CLIENT ORDER No			
APPROVED		DATE		MATERIAL			
SCALE	REDUCED	CAD PLOT		FINISH			

2 REV PJW 23/05/05 TAPPED HOLE OPTION ADDED
1 REV BY DATE DESCRIPTION or CHANGE NOTE No

SHEET No	1	ISSUE	1
OF	1		

36 UNI 220 (OPTION 1)
40X3X12 DIN 5480 (OPTION 7)
OTHER OPTIONS ARE AVAILABLE